

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26

1. A security article comprising:  
a light transmissive substrate having a first surface and an opposing second surface, the first surface having an optical interference pattern;  
a color shifting optical coating on the second surface of the substrate, the optical coating providing an observable color shift as the angle of incident light or viewing angle changes; and  
an adhesive layer on the optical coating.

2. The security article of claim 1, wherein the substrate comprises a plastic material.

3. The security article of claim 2, wherein the plastic material is selected from the group consisting of polyethylene terephthalate, polycarbonate, polyvinyl chloride, polyacrylates, polyacrylonitrile, polystyrene, polypropylene, cellulose diacetate, cellulose triacetate, polydicyclopentadiene, and mixtures and copolymers thereof.

4. The security article of claim 1, wherein the optical interference pattern is selected from the group consisting of a diffraction grating pattern, refraction pattern, holographic image pattern, corner cube reflector, zero order diffraction pattern, moiré pattern, and combinations thereof.

5. The security article of claim 1, wherein the optical interference pattern is selected from the group consisting of a Kinegram® device, and a Pixelgram® device.

[illegible]

12. The security article of claim 1, wherein the color shifting optical coating is a multilayer optical interference film including an absorber layer on the second surface of the substrate, a dielectric layer on the absorber layer, a thin shear layer on the dielectric layer, and a reflector layer on the shear layer.

13. The security article of claim 12, wherein the shear layer has a thickness from about 50 Å to about 200 Å.

14. The security article of claim 1, wherein the combination of the optical interference pattern and the color shifting optical coating produce unique colors with viewing angle changes not achievable with either the optical interference pattern or the color shifting optical coating alone.

15. The security article of claim 1, wherein the color shifting optical coating includes a laser ablated image formed therein.

16. The security article of claim 15, wherein the laser ablated image is selected from the group consisting of digital images, bar codes, covert data, and combinations thereof.

17. The security article of claim 1, wherein the color shifting optical coating includes a laser scribed number.

18. The security article of claim 15, wherein the color shifting optical coating further includes a laser scribed number.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26

19. A security article comprising:  
a light transmissive substrate having a first surface and an opposing second surface, the first surface having an optical interference pattern;  
a color shifting optical coating on a carrier sheet, the optical coating laminated to the second surface of the substrate by an adhesive layer, the optical coating providing an observable color shift as the angle of incident light or viewing angle changes.

20. The security article of claim 19, wherein the optical interference pattern is selected from the group consisting of a diffraction grating pattern, refraction pattern, holographic image pattern, corner cube reflector, zero order diffraction pattern, moiré pattern, and combinations thereof.

21. The security article of claim 19, wherein the optical interference pattern is selected from the group consisting of a Kinegram® device, and a Pixelgram® device.

22. The security article of claim 19, wherein the optical interference pattern is a light interference pattern based on microstructures having dimensions of from about 0.1 μm to about 10 μm.

23. The security article of claim 19, wherein the color shifting optical coating is a multilayer optical interference film including a reflector layer on the carrier sheet, a dielectric layer on the reflector layer, and an absorber layer on the dielectric layer.

24. The security article of claim 19, wherein the color shifting optical coating is a multilayer optical interference film including a first absorber layer on the carrier sheet, a dielectric layer on the first absorber layer, and a second absorber layer on the dielectric layer.

25. The security article of claim 19, wherein the color shifting optical coating is a multilayer optical interference film comprising alternating layers of low and high index of refraction dielectric layers.

26. The security article of claim 19, wherein the color shifting optical coating comprises a plurality of multilayer optical interference flakes dispersed in a polymeric medium.

27. The security article of claim 19, wherein the color shifting optical coating is a multilayer optical interference film including a reflector layer on the carrier sheet, a thin shear layer on the reflector layer, a dielectric layer on the shear layer, and an absorber layer on the dielectric layer.

28. The security article of claim 27, wherein the shear layer has a thickness from about 50 Å to about 200 Å.

29. The security article of claim 19, wherein the color shifting optical coating includes a laser ablated image formed therein.

30. The security article of claim 29, wherein the laser ablated image is selected from the group consisting of digital images, bar codes, covert data, and combinations thereof.

31. The security article of claim 19, wherein the color shifting optical coating includes a laser scribed number.

32. The security article of claim 29, wherein the color shifting optical coating further includes a laser scribed number.

33. The security article of claim 29, further comprising a covert resistive layer on the first surface of the substrate.

34. The security article of claim 33, wherein the covert resistive layer is composed of a transparent conductive material selected from the group consisting of indium tin oxide, indium oxide, cadmium tin oxide, and combinations thereof.

1 35. A security article comprising:

2 a light transmissive substrate having a first surface and an opposing second  
3 surface, the first surface having an optical interference pattern;

4 a color shifting optical coating on a carrier sheet, the optical coating  
5 laminated to the first surface of the substrate by an adhesive layer, the optical coating  
6 providing an observable color shift as the angle of incident light or viewing angle  
7 changes.  
8

9 36. The security article of claim 35, wherein the optical interference pattern is  
10 selected from the group consisting of a diffraction grating pattern, refraction pattern,  
11 holographic image pattern, corner cube reflector, zero order diffraction pattern, moiré pattern,  
12 and combinations thereof.  
13

14 37. The security article of claim 35, wherein the optical interference pattern is  
15 selected from the group consisting of a Kinegram® device, and a Pixelgram® device.  
16

17 38. The security article of claim 35, wherein the optical interference pattern is a  
18 light interference pattern based on microstructures having dimensions of from about 0.1  $\mu\text{m}$   
19 to about 10  $\mu\text{m}$ .  
20

21 39. The security article of claim 35, wherein the color shifting optical coating is  
22 a multilayer optical interference film including a reflector layer on the carrier sheet, a  
23 dielectric layer on the reflector layer, and an absorber layer on the dielectric layer.  
24  
25  
26

1           40.     The security article of claim 35, wherein the color shifting optical coating is  
2     a multilayer optical interference film including a first absorber layer on the carrier sheet, a  
3     dielectric layer on the first absorber layer, and a second absorber layer on the dielectric layer.

4  
5           41.     The security article of claim 35, wherein the color shifting optical coating is  
6     a multilayer optical interference film comprising alternating layers of low and high index of  
7     refraction dielectric layers.

8  
9           42.     The security article of claim 35, wherein the color shifting optical coating  
10    comprises a plurality of multilayer optical interference flakes dispersed in a polymeric  
11    medium.

12  
13          43.     The security article of claim 35, wherein the color shifting optical coating  
14    includes a laser ablated image formed therein.

15  
16          44.     The security article of claim 35, wherein the color shifting optical coating  
17    includes a laser scribed number.

18  
19          45.     The security article of claim 43, wherein the color shifting optical coating  
20    further includes a laser scribed number.

21  
22          46.     The security article of claim 43, further comprising a covert resistive layer on  
23    the second surface of the substrate.



1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26

47. A pre laminate color shifting structure comprising:  
a light transmissive carrier sheet;  
a color shifting optical coating formed on the carrier sheet, the optical coating  
providing an observable color shift as the angle of incident light or viewing angle  
changes; and  
a laser ablated image and/or a laser scribed number formed in the optical  
coating.

48. The pre laminate color shifting structure of claim 47, wherein the laser ablated  
image is selected from the group consisting of digital images, bar codes, covert data, and  
combinations thereof.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26

2

4

9

11

15

20

A PROFESSIONAL CORPORATION  
ATTORNEYS AT LAW  
1000 EAGLE GATE TOWER  
60 EAST SOUTH TEMPLE  
SALT LAKE CITY, UTAH 84111

54. A method of forming a security article, comprising the steps of:  
obtaining a master shim having a first surface with a holographic or diffractive pattern thereon;  
forming a color shifting optical coating on the first surface of the master shim so as to conform to the shape of the holographic or diffractive pattern;  
affixing a carrier substrate layer to the optical coating; and  
removing the optical coating and carrier substrate layer from the master shim to produce a security article with the holographic or diffractive pattern replicated in the optical coating, the optical coating providing an observable color shift to the security article as the angle of incident light or viewing angle changes.

55. The method of claim 54, wherein the master shim is composed of a metallic material selected from the group consisting of nickel, tin, chromium, and combinations thereof.

56. The method of claim 54, wherein the color shifting optical coating is a multilayer optical interference film including a dielectric layer interposed between two absorber layers.

57. The method of claim 54, wherein the color shifting optical coating is a multilayer optical interference film including an absorber layer, a dielectric layer, and a reflector layer.

58. The method of claim 54, wherein the color shifting optical coating is a multilayer optical interference film comprising alternating layers of low and high index of refraction dielectric layers.

1 59. The method of claim 54, wherein the color shifting optical coating is formed  
2 by physical vapor deposition.

3  
4 60. The method of claim 54, wherein the carrier substrate layer comprises a  
5 plastic sheet.

6  
7 61. The method of claim 54, further comprising the step of attaching the security  
8 article to an object with an adhesive.

9  
10 62. The method of claim 61, wherein the adhesive is a pressure sensitive  
11 adhesive.

12  
13 63. The method of claim 61, wherein the object is selected from the group  
14 consisting of security documents, monetary currency, credit cards, identification cards,  
15 passports, and merchandise packaging.

16  
17 64. A security article formed by the method recited in claim 54.

18  
19 65. A security article comprising a holographic or diffractive pattern in a  
20 multilayer thin film optical interference stack.

Sub  
DL

Sub  
DL

66. A hot stamp structure for use in attaching a security article to an object,  
comprising:  
a carrier sheet;  
a release layer on the carrier sheet;  
a light transmissive substrate on the release layer, the substrate having an  
optical interference pattern thereon;  
a color shifting optical coating on the substrate, the optical coating providing  
an observable color shift as the angle of incident light or viewing angle changes; and  
an adhesive layer on the optical coating.

67. The hot stamp structure of claim 66, wherein the carrier sheet comprises a  
plastic material.

68. The hot stamp structure of claim 66, wherein the release layer comprises a  
material selected from the group consisting of polyvinyl chloride, polystyrene, chlorinated  
rubber, acrylonitrile-butadiene-styrene copolymer, nitrocellulose, methyl methacrylate,  
acrylic copolymers, fatty acids, waxes, gums, gels, and mixtures thereof.

69. The hot stamp structure of claim 66, wherein the color shifting optical coating  
is a multilayer optical interference film including a dielectric layer interposed between two  
absorber layers.

70. The hot stamp structure of claim 66, wherein the color shifting optical coating  
is a multilayer optical interference film including an absorber layer, a dielectric layer adjacent  
to the absorber layer, and a reflector layer adjacent to the dielectric layer.

1           71.     The hot stamp structure of claim 66, wherein the color shifting optical coating  
2 is a multilayer optical interference film comprising alternating layers of low and high index  
3 of refraction dielectric layers.

4  
5           72.     The hot stamp structure of claim 66, wherein the color shifting optical coating  
6 comprises a plurality of multilayer optical interference flakes dispersed in a polymeric  
7 medium.

8  
9           73.     The hot stamp structure of claim 66, wherein the color shifting optical coating  
10 includes a laser ablated image formed therein.

11  
12           74.     The hot stamp structure of claim 66, wherein the color shifting optical coating  
13 includes a laser scribed number.

14  
15           75.     The hot stamp structure of claim 73, wherein the color shifting optical coating  
16 further includes a laser scribed number.

17  
18           76.     The hot stamp structure of claim 66, wherein the adhesive layer is a thermally  
19 activated adhesive comprising a material selected from the group consisting of acrylic-based  
20 polymers, ethylene vinyl acetate, polyamides, and combinations thereof.

21  
22           77.     The hot stamp structure of claim 66, wherein the adhesive layer comprises a  
23 UV activated adhesive.

78. A method of attaching a security article to an object, comprising the steps of:  
providing a hot stamp structure, comprising:  
a carrier sheet;  
a release layer on the carrier sheet;  
a light transmissive substrate on the release layer, the substrate having  
an optical interference pattern thereon;  
a color shifting optical coating on the substrate, the optical coating  
providing an observable color shift as the angle of incident light or viewing  
angle changes; and  
a thermally activated adhesive layer on the optical coating;  
pressing the hot stamp structure onto a surface of an object which is heated  
to a temperature to provide a bond between the object and the adhesive layer; and  
removing the carrier sheet from the substrate to reveal a security article  
attached to the object.

Add H7  
Add CS  
Add D11